



Designation: D6230 – 21^{ε1}

Standard Practices for Monitoring Earth or Structural Movement Using Inclinometers¹

This standard is issued under the fixed designation D6230; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

^{ε1} NOTE—Minor corrections were editorially made throughout in July 2021.

1. Scope*

1.1 This standard covers the use of inclinometers to monitor the internal movement of ground, or lateral movement of subsurface structures. The standard covers types of instruments, installation procedures, operating procedures, and maintenance requirements. The standard also provides formulae for data reduction.

1.2 All observed and calculated values shall conform to the guidelines for significant digits and rounding established in Practice D6026 unless superseded by this standard.

1.2.1 The procedures used to specify how data are collected, recorded or calculated in this standard are regarded as the industry standard. In addition, they are representative of the significant digits that generally should be retained. The procedures used do not consider material variation, purpose for obtaining the data, special purpose studies, or any considerations for the user's objectives; it is common practice to increase or reduce significant digits of reported data to be commensurate with these considerations. It is beyond the scope of this standard to consider significant digits used in analytical methods for engineering design.

1.3 *Units*—The values stated in SI units are to be regarded as the standard. The inch-pound units given in parentheses are for information only. Reporting of test results in units other than SI shall not be regarded as nonconformance with this standard.

1.4 This standard offers an organized collection of information or a series of options and does not recommend a specific course of action. This document cannot replace education or experience and should be used in conjunction with professional judgment. Not all aspects of this standard may be applicable in all circumstances. This ASTM standard is not intended to represent or replace the standard of care by which the adequacy

of a given professional service must be judged, nor should this document be applied without consideration of a project's many unique aspects. The word "Standard" in the title of this document means only that the document has been approved through the ASTM consensus process.

1.5 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.*

1.6 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

2. Referenced Documents

2.1 ASTM Standards:²

- D653 Terminology Relating to Soil, Rock, and Contained Fluids
- D3740 Practice for Minimum Requirements for Agencies Engaged in Testing and/or Inspection of Soil and Rock as Used in Engineering Design and Construction
- D3966/D3966M Test Methods for Deep Foundations Under Lateral Load
- D6026 Practice for Using Significant Digits and Data Records in Geotechnical Data
- D7299 Practice for Verifying Performance of a Vertical Inclinometer Probe

3. Terminology

3.1 For definitions of common technical terms used in this standard, refer to Terminology D653.

¹ This practice is under the jurisdiction of ASTM Committee D18 on Soil and Rock and is the direct responsibility of Subcommittee D18.23 on Field Instrumentation.

Current edition approved June 1, 2021. Published June 2021. Originally approved in 1998. Last previous edition approved in 2013 as D6230 – 13. DOI: 10.1520/D6230-21E01.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

*A Summary of Changes section appears at the end of this standard

3.2 Definitions of Terms Specific to This Standard:

3.2.1 *inclinometer casing, n*—a (typically segmented) pipe or casing with grooves specific for the type of inclinometer being used.

3.2.1.1 *Discussion*—Casing is typically made of plastic, aluminum alloy, or fiberglass.

3.2.2 *inclinometer probe, n*—an instrument comprised of a downhole probe which uses internal sensors to detect its own orientation relative to the force of gravity, with a wheel assembly for lowering into the inclinometer casing along the alignment grooves, connected by a cable to a readout or datalogger at the surface.

3.2.3 *in-place inclinometer gauge (IPI gauge), n*—an inclinometer probe which is designed to be installed at a fixed depth in an inclinometer casing, typically in an array of multiple units with known spacing and kept in place for the duration of the monitoring period.

3.2.4 *spiral probe, n*—a wheeled probe that tracks alignment differences between its top and bottom wheels, whose readings measure the spiraling twist of an inclinometer casing installation.

4. Significance and Use

4.1 An inclinometer is a deformation monitoring system, which uses a grooved pipe or casing with internal longitudinal grooves aligned with the anticipated direction of movement, installed in either a soil/rock mass or a geotechnical structural element. The inclinometer casing can be surveyed with a single traversing probe or with an array of in-place inclinometer (IPI) gauges connected to a data logger. The measurement and calculation of deformation normal to the axis of the inclinometer casing is done by passing a probe along the length of this pipe or placement of a sensor array, guided by the internal grooves. The probe or sensor array measures the inclination of the pipe, usually in two orthogonal directions 90° apart (X- and Y-direction) with respect to the axis of the casing (Z-direction, usually the line of gravity). Measurements are converted to distances using trigonometric functions. Successive surveys compared with an initial survey give differences in position and indicate deformation normal to the axis of the inclinometer casing. In most cases the inclinometer casing is installed in a near-vertical hole, and the measurements indicate subsurface horizontal deformation. In some cases, the inclinometer casing is installed horizontally, and the measurements indicate vertical deformation.

4.2 Inclinometers are also called slope inclinometers or slope indicators. Typical applications include measuring the rate and direction of landslide movement and locating the zone of shearing, monitoring the magnitude and rate of horizontal movements for embankments and excavations, monitoring the settlement and lateral spread beneath tanks and embankments, and monitoring the deflection of bulkheads, piles or structural walls.

NOTE 1—The precision of this standard is dependent on the competence of the personnel performing it and the suitability of the equipment and facilities used. Agencies that meet the criteria of Practice D3740 are generally considered capable of competent and objective testing. Users of this standard are cautioned that compliance with Practice D3740 does not

in itself ensure reliable results. Reliable testing depends on many factors; Practice D3740 provides a means of evaluating some of those factors.

5. Apparatus

5.1 *Method A*—The traveling-probe-type inclinometer system consists of an inclinometer probe, typically utilizing microelectromechanical systems (MEMS) technology sensors, which give the inclination of the probe digitally. Biaxial probes contain two sensors oriented 90° apart to permit readings in orthogonal directions at the same time. Other sensor types, such as ones based on force balance accelerometers, which give a voltage output that is proportional to inclination of the probe, may also be used. The probe(s) can have an analog or digital output. Use of a single uniaxial or biaxial probe pulled through the casing while being sampled is designated as Method “A.” A portable readout unit, connected via cable or wirelessly, is used to display probe inclination and record the inclination data.

5.1.1 An electrical cable with distance markings connects the probe and power supply (which may also include the readout). Fig. 1 illustrates a typical set of components. The cable should include a clamp to prevent the probe from falling down the borehole. For deep holes a hoist or winch may be required.

5.2 *Method B*—The in-place inclinometer (IPI) array is a set of gauges which are installed in the casing at fixed distances apart, using spacer rods or pipes. These gauges may be individual units with connecting and spacing elements between them, or may consist of a continuous assembly. Some models of in-place inclinometers may be held in place using guide wheels in grooved casings. Fig. 2 illustrates two types of common in-place inclinometer assemblies. The left schematic in Fig. 2 is an example of multiple probes assembled together to form a single in-place inclinometer installation, with wheels to align in a grooved casing. Gauge length for this assembly is measured wheel to wheel. The right schematic in Fig. 2 is an example of a continuous in-place inclinometer with no wheels. Gauge length in this case is measured joint center to joint center. Use of an in-place inclinometer array which is sampled while stationary in the casing is designated as Method “B.” Other sensor types, including ones mentioned in Method “A” above and also ones based on vibrating wire technology, may be used. The use of an array may be more applicable in a scenario where observations need to be taken relatively rapidly, such as during a lateral pile load test (see Standard D3966/D3966M), or where observations need to be taken continually over long periods of time, such as monitoring shoring for excess deformation during excavation. Individual instruments in the array may be uniaxial or biaxial.

6. Procedure

6.1 Installation of Casing in a Borehole:

6.1.1 Select casing materials that are compatible with the environmental conditions at the installation. Select casing size consistent with the specific measurement requirements and conditions for the job. Store casing materials in a safe, secure place to prevent damage. Sunlight may damage plastic casing. High and low pH may damage metal casing.