



Designation: D6537 – 00 (Reapproved 2021)

Standard Practice for Instrumented Package Shock Testing For Determination of Package Performance¹

This standard is issued under the fixed designation D6537; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This practice covers methods for obtaining measured shock responses using instrumentation for an actual or simulated product package system when subjected to defined shock inputs to measure package performance.

1.2 This practice establishes methods for obtaining measured shock data for use with shock and impact test methods. It is not intended as a substitute for performance testing of shipping containers and systems such as Practice [D4169](#).

1.3 This practice will address acceleration measuring techniques. Other ways of measuring shock impacts, such as high speed video, are not covered by this practice.

1.4 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.*

1.5 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

2. Referenced Documents

2.1 ASTM Standards:²

[D996](#) Terminology of Packaging and Distribution Environments

[D3332](#) Test Methods for Mechanical-Shock Fragility of Products, Using Shock Machines

[D4003](#) Test Methods for Programmable Horizontal Impact Test for Shipping Containers and Systems

[D4169](#) Practice for Performance Testing of Shipping Containers and Systems

[D5276](#) Test Method for Drop Test of Loaded Containers by Free Fall

[D5277](#) Test Method for Performing Programmed Horizontal Impacts Using an Inclined Impact Tester

[D5487](#) Test Method for Simulated Drop of Loaded Containers by Shock Machines

[D6055](#) Test Methods for Mechanical Handling of Unitized Loads and Large Shipping Cases and Crates

[D6179](#) Test Methods for Rough Handling of Unitized Loads and Large Shipping Cases and Crates

2.2 ISO Standard:

[10012](#) Quality Assurance for Measuring Equipment³

3. Terminology

3.1 Definitions:

3.1.1 General definitions for packaging and distribution are found in Terminology [D996](#).

3.2 Definitions of Terms Specific to This Standard:

3.2.1 *accelerometer, n*—a sensor that converts acceleration into a proportional electric signal for measurement.

3.2.2 *coefficient of restitution, n*—the ratio of the rebound velocity to the impact velocity.

3.2.3 *complex waveform, n*—acceleration versus time graph representing the responses of many different spring/mass systems when subjected to an impact. Also referred to as a complex shock-pulse.

3.2.4 *faired acceleration, n*—the amplitude representing the primary or intended response system in a complex shock pulse.

3.2.5 *fairing, n*—the graphical smoothing of a recorded pulse by visually estimating the amplitude of the primary waveform when high frequency responses are also present.

3.2.6 *peak acceleration, n*—the maximum absolute value of acceleration which occurred during the shock pulse.

¹ This practice is under the jurisdiction of ASTM Committee [D10](#) on Packaging and is the direct responsibility of Subcommittee [D10.13](#) on Interior Packaging.

Current edition approved Oct. 1, 2021. Published November 2021. Originally approved in 2000. Last previous edition approved in 2014 as D6537 – 00 (2014). DOI: 10.1520/D6537-00R21.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

³ Available from American National Standards Institute (ANSI), 25 W. 43rd St., 4th Floor, New York, NY 10036, <http://www.ansi.org>.

3.2.7 *primary waveform, n*—acceleration versus time graph representing the response of the spring/mass system of interest when subjected to an impact. Also referred to as a primary shock-pulse.

3.2.8 *pulse duration, n*—the amount of time the shock acceleration is beyond a reference level. This level is generally taken as 10 % of the pulse peak acceleration (not the zero baseline) to most accurately represent the effective duration and frequency of the pulse.

3.2.9 *velocity change, n*—the sum of the velocity at impact and the rebound velocity.

4. Significance and Use

4.1 This practice is intended to provide the user with a process to obtain data on package performance when a packaged product is subjected to shock. These measures can be used to quantify or qualify a package system.

4.2 Data from this practice may provide a measure of a package's ability to mitigate the various levels of shipping shock or impact hazards. These measures may be used to prescribe a mode of shipping and handling that will not induce damage to the packaged product or to define the required levels of protection that must be provided by its packaging.

4.3 This practice could potentially be used in conjunction with the data derived from Test Method **D3332** (Method B) for optimizing cushion design.

4.4 This practice obtains data at the interface of the product and package (coupled) or element response, depending on the intent of the user (see **10.1** and **10.1.1**).

5. Apparatus

5.1 Shock or impact apparatus shall be as described in the established shock or impact method used. Examples of shock and impact apparatuses are described in Test Methods **D4003**, **D5276**, **D5277**, **D5487** and **D6055**.

5.2 Instrumentation:

5.2.1 *Instrumentation System*—Accelerometer(s), cables, signal conditioner, and a data acquisition system are required to record acceleration versus time histories. The instrumentation system shall have the following minimum properties:

5.2.1.1 Frequency response from at least 2 Hz to at least 1000 Hz.

5.2.1.2 Accuracy reading to be within ± 5 % of the actual value.

5.2.1.3 *Accelerometers*—An appropriate accelerometer shall be used that is capable of measuring the acceleration input over the desired amplitude frequency and temperature range. Avoid accelerometers where the mass characteristics of the accelerometer, including any attachments to it (mountings, cables, etc.), will affect the weight or stiffness of the surface to which it is attached.

NOTE 1—A false reading of the mounting structure or unnecessary high frequency responses will occur if the mass of the accelerometer is too large in relation to the mounting surface. The mass characteristics of the

accelerometer assembly should be less than $1/10^{\text{th}}$ the mass of the structure being measured (**1**).⁴

5.2.1.4 Cross axis sensitivity less than 5 % of actual value.

5.2.1.5 *Cabling*—Use cables that are suitable to the system used. Accelerometer cables should be as lightweight and flexible as possible to avoid mass loading on the accelerometer or structure being tested. Cable length may alter the desired signal depending on the application and type of accelerometer used. Refer to manufacturers' recommendations for appropriate cable type and length because various accelerometer types require special cables and are not necessarily interchangeable.

6. Sampling

6.1 Sampling procedures and the number of test specimens depends on the specific purposes and needs of the testing. Refer to the sampling procedure for the standard test method chosen.

7. Test Specimen

7.1 *Option 1*—Actual contents and package.

7.1.1 Use this option to evaluate the protective capability of the package intended for shipment and when the actual contents are available. Testing a prototype package may yield results that differ from a production manufactured package. Care should be taken to ensure that the construction and materials of the prototype are representative of a production package. Re-testing may be required with a production package to verify earlier test results. (**Warning**—Damage to the test specimen may result from shock or impact testing.)

7.1.2 The contents may or may not be operational or in calibration.

7.2 *Option 2*—Simulated contents and package.

7.2.1 Use this option to evaluate the package when access to the actual contents is prohibitive because of availability, excessive cost or hazardous nature. This option may also be desirable to eliminate or minimize high frequency responses that the actual product may produce.

7.2.2 A mock-up simulating the actual product with respect to dimensions, center of gravity, moment of inertia and other product characteristics may be used.

7.2.3 A dummy load may be used to represent the loading characteristics of the actual product within the package.

7.2.4 Mock-ups and dummy loads are to be fabricated from rigid, non-responsive materials such as wood, plastic, modeling foam, aluminum, or steel, and be durable enough to withstand the intended impacts without failing. A mock-up load may use part(s) of the actual product with modifications to replicate the actual product or be fabricated entirely from other materials.

7.3 Minor modifications may be made to the product or package to accommodate accelerometers, cabling, or to observe the product during the test. Such modifications are allowed as long as they do not affect the test results.

7.4 Care must be taken to ensure that no degradation has occurred to the package if the test packages have been shipped

⁴ The boldface numbers in parentheses refer to a list of references at the end of this standard.