



Designation: D7952 – 15 (Reapproved 2021)

Standard Test Method for Measuring Aspiration Potential of Aerosol Products¹

This standard is issued under the fixed designation D7952; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This test method covers a small-scale laboratory procedure to determine the aspiration potential of aerosol products by determining spray pattern and aerosol deposition rates.

1.2 This test method has been developed to address a need to identify which aerosol products may present an aspiration risk such that special labeling and/or child-resistant packaging would be appropriate. Studies based on this method may allow the development of a practice to identify such aerosol products.

1.3 Although this method may be useful for testing non-pressurized aerosol products, its development has been limited to testing pressurized aerosols.

1.4 The values stated in inch-pound units are to be regarded as standard. The values given in parentheses are mathematical conversions to SI units that are provided for information only and are not considered standard.

1.5 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.*

1.6 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

2. Terminology

2.1 Definitions:

2.1.1 *aerosol product, n*—a product that dispenses liquid as an aerosol.

2.1.2 *ballistic stream (or stream), n*—a stream pattern that deposits entirely in the test cup.

2.1.3 *cone spray, n*—spray pattern where the bottom of the test cup is completely covered during a 5 to 7 s test but a portion of the aerosol is deposited outside of the cup during the entire test.

2.1.4 *deposition rate, n*—the amount of aerosol (in grams) that dispenses in a test cup in one second.

2.1.5 *mist, n*—spray pattern where the aerosol only partially covers the bottom of the test cup during a 5 to 7 s test.

2.1.6 *pressurized aerosol product, n*—an aerosol product that is self-pressurized and does not require pumping to dispense an aerosol.

2.1.7 *spray pattern, n*—the pattern in which an aerosol is dispensed and deposited.

3. Summary of Test Method

3.1 After shaking and discarding 5 s worth of spray, the test aerosol is sprayed onto a test cup held in place with sticky wax from an aligning apparatus (see Fig. 1) for 5 to 7 s. The test cup is weighed before the test and within 60 s after concluding the test.

4. Significance and Use

4.1 This test method provides a means of measuring whether or not an aerosol product may present an aspiration risk if a dispensed aerosol gets into one's mouth.

4.2 The degree of risk for aspiration of an aerosol depends both on spray pattern as well as aerosol deposition rate.²

4.3 This test method will be used to determine the need for child-resistant packaging of aerosol products.

5. Apparatus

5.1 *Scale*, sensitive to 0.0001 g.

5.2 *6.0 cm Aluminum Weighing Cups*.

5.3 *Jeweler's Sticky Wax*.

5.4 *Stopwatch*, sensitive to 1/100 th s.

5.5 *Plexiglas Sheet*, 2 by 3 ft.

¹ This test method is under the jurisdiction of ASTM Committee D01 on Paint and Related Coatings, Materials, and Applications and is the direct responsibility of Subcommittee D01.57 on Artist Paints and Related Materials.

Current edition approved Nov. 1, 2021. Published November 2021. Originally approved in 2015. Last previous edition approved in 2015 as D7952 – 15. DOI: 10.1520/D7952-15R21.

² Supporting data have been filed at ASTM International Headquarters and may be obtained by requesting Research Report RR:D01-1179. Contact ASTM Customer Service at service@astm.org.