



Designation: D8076 – 21b

Standard Specification for 100 Research Octane Number Test Fuel for Automotive Spark-Ignition Engines¹

This standard is issued under the fixed designation D8076; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope*

1.1 This specification covers the requirements of a high octane number test fuel suitable for spark-ignition engines to be utilized in ground vehicles that will require 100 research octane number (RON) minimum rated fuel.

1.1.1 The fuels described by this specification are intended for developing technologies that lead to reduced vehicle energy consumption, such as higher compression ratio, higher power density, increased turbocharger boost pressure, smaller swept displacement volume, and operation at lower engine speeds.

1.1.2 The fuels described in this test fuel specification may not meet all of the performance or regulatory requirements for use in vehicles using commercial gasoline.

1.2 The fuels covered in this specification may contain oxygenates, such as alcohols and ethers, up to 50 % by volume. This specification covers fuels that may contain both fossil and bio-derived components.

1.3 This specification provides a description of high RON test fuel for automotive spark-ignition engines that are not currently in the marketplace but are being developed and require a defined standard test fuel. The high RON fuel could become available in the marketplace if/when such engines are introduced in commerce. The specification is under continuous review, which can result in revisions based on changes in fuel, automotive requirements, or test methods, or a combination thereof. All users of this specification, therefore, should refer to the latest edition.

NOTE 1—If there is any doubt as to the latest edition of Specification D8076, contact ASTM International Headquarters.

1.4 The values stated in SI units are the standard.

1.4.1 *Exception*—Non-SI values are provided for information only. U.S. federal regulations frequently specify non-SI units.

1.5 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the*

responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.

1.6 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

2. Referenced Documents

2.1 *ASTM Standards:*²

D86 Test Method for Distillation of Petroleum Products and Liquid Fuels at Atmospheric Pressure

D130 Test Method for Corrosiveness to Copper from Petroleum Products by Copper Strip Test

D381 Test Method for Gum Content in Fuels by Jet Evaporation

D525 Test Method for Oxidation Stability of Gasoline (Induction Period Method)

D1152 Specification for Methanol (Methyl Alcohol) (Withdrawn 2021)³

D1266 Test Method for Sulfur in Petroleum Products (Lamp Method)

D2622 Test Method for Sulfur in Petroleum Products by Wavelength Dispersive X-ray Fluorescence Spectrometry

D2699 Test Method for Research Octane Number of Spark-Ignition Engine Fuel

D2700 Test Method for Motor Octane Number of Spark-Ignition Engine Fuel

D3120 Test Method for Trace Quantities of Sulfur in Light Liquid Petroleum Hydrocarbons by Oxidative Microcoulometry

D3237 Test Method for Lead in Gasoline by Atomic Absorption Spectroscopy

D3831 Test Method for Manganese in Gasoline By Atomic

¹ This specification is under the jurisdiction of ASTM Committee D02 on Petroleum Products, Liquid Fuels, and Lubricants and is the direct responsibility of Subcommittee D02.A0.01 on Gasoline and Gasoline-Oxygenate Blends.

Current edition approved Oct. 1, 2021. Published October 2021. Originally approved in 2017. Last previous edition approved in 2021 as D8076 – 21a. DOI: 10.1520/D8076-21B.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

³ The last approved version of this historical standard is referenced on www.astm.org.

*A Summary of Changes section appears at the end of this standard

Absorption Spectroscopy

- D4057** Practice for Manual Sampling of Petroleum and Petroleum Products
- D4175** Terminology Relating to Petroleum Products, Liquid Fuels, and Lubricants
- D4176** Test Method for Free Water and Particulate Contamination in Distillate Fuels (Visual Inspection Procedures)
- D4177** Practice for Automatic Sampling of Petroleum and Petroleum Products
- D4306** Practice for Aviation Fuel Sample Containers for Tests Affected by Trace Contamination
- D4806** Specification for Denatured Fuel Ethanol for Blending with Gasolines for Use as Automotive Spark-Ignition Engine Fuel
- D4814** Specification for Automotive Spark-Ignition Engine Fuel
- D4815** Test Method for Determination of MTBE, ETBE, TAME, DIPE, tertiary-Amyl Alcohol and C₁ to C₄ Alcohols in Gasoline by Gas Chromatography
- D4953** Test Method for Vapor Pressure of Gasoline and Gasoline-Oxygenate Blends (Dry Method)
- D5059** Test Methods for Lead and Manganese in Gasoline by X-Ray Fluorescence Spectroscopy
- D5191** Test Method for Vapor Pressure of Petroleum Products and Liquid Fuels (Mini Method)
- D5453** Test Method for Determination of Total Sulfur in Light Hydrocarbons, Spark Ignition Engine Fuel, Diesel Engine Fuel, and Engine Oil by Ultraviolet Fluorescence
- D5482** Test Method for Vapor Pressure of Petroleum Products and Liquid Fuels (Mini Method—Atmospheric)
- D5599** Test Method for Determination of Oxygenates in Gasoline by Gas Chromatography and Oxygen Selective Flame Ionization Detection
- D5842** Practice for Sampling and Handling of Fuels for Volatility Measurement
- D5845** Test Method for Determination of MTBE, ETBE, TAME, DIPE, Methanol, Ethanol and *tert*-Butanol in Gasoline by Infrared Spectroscopy
- D5854** Practice for Mixing and Handling of Liquid Samples of Petroleum and Petroleum Products
- D5983** Specification for Methyl Tertiary-Butyl Ether (MTBE) for Blending With Gasolines for Use as Automotive Spark-Ignition Engine Fuel
- D6378** Test Method for Determination of Vapor Pressure (VP_x) of Petroleum Products, Hydrocarbons, and Hydrocarbon-Oxygenate Mixtures (Triple Expansion Method)
- D6550** Test Method for Determination of Olefin Content of Gasolines by Supercritical-Fluid Chromatography
- D7039** Test Method for Sulfur in Gasoline, Diesel Fuel, Jet Fuel, Kerosine, Biodiesel, Biodiesel Blends, and Gasoline-Ethanol Blends by Monochromatic Wavelength Dispersive X-ray Fluorescence Spectrometry
- D7220** Test Method for Sulfur in Automotive, Heating, and Jet Fuels by Monochromatic Energy Dispersive X-ray Fluorescence Spectrometry

- D7319** Test Method for Determination of Existent and Potential Sulfate and Inorganic Chloride in Fuel Ethanol and Butanol by Direct Injection Suppressed Ion Chromatography
- D7328** Test Method for Determination of Existent and Potential Inorganic Sulfate and Total Inorganic Chloride in Fuel Ethanol by Ion Chromatography Using Aqueous Sample Injection
- D7618** Specification for Ethyl Tertiary-Butyl Ether (ETBE) for Blending with Aviation Spark-Ignition Engine Fuel
- D7667** Test Method for Determination of Corrosiveness to Silver by Automotive Spark-Ignition Engine Fuel—Thin Silver Strip Method
- D7671** Test Method for Corrosiveness to Silver by Automotive Spark-Ignition Engine Fuel—Silver Strip Method
- D7862** Specification for Butanol for Blending with Gasoline for Use as Automotive Spark-Ignition Engine Fuel
- E29** Practice for Using Significant Digits in Test Data to Determine Conformance with Specifications

2.2 Government Regulations:

- United States Code of Federal Regulations Title 40 Protection of Environment**⁴
- California Code of Regulations Title 17—Public Health—Section 60100–60114 Description of California Air Basins**⁵

2.3 Other Documents:

- CRC Report No. 660 Fuel Antiknock Quality—Engine Response to RON Versus MON Scoping Tests, Final Report, May 2011**⁶

3. Terminology

- 3.1 For general terminology, refer to Terminology **D4175**.

3.2 Definitions:

3.2.1 *dry vapor pressure equivalent (DVPE)*, *n*—value calculated by a defined correlation equation that is expected to be comparable to the vapor pressure value obtained by Test Method **D4953**, Procedure A. **D4953**

3.2.2 *gasoline*, *n*—a volatile mixture of liquid hydrocarbons, generally containing small amounts of additives, suitable for use as a fuel in spark-ignition, internal combustion engines. **D4814**

3.2.3 *gasoline-oxygenate blend*, *n*—a fuel consisting primarily of gasoline along with a substantial amount (more than 0.35 % by mass oxygen) of one or more oxygenates. **D4814**

3.2.4 *octane sensitivity*, *n*—the mathematical difference between research octane number (RON) and motor octane number (MON) (octane sensitivity = RON – MON).

3.2.4.1 *Discussion*—A typical value for sensitivity is 6 to 10. A larger value is referred to as high sensitivity.

⁴ Available from U.S. Government Printing Office, Superintendent of Documents, 732 N. Capitol St., NW, Washington, DC 20401-0001, or electronically at <https://www.govinfo.gov/app/collection/cfr>.

⁵ Available from California's Office of Administrative Law, <https://oal.ca.gov/publications/ccr/>.

⁶ Available from Coordinating Research Council, 5755 North Point Parkway, Suite 265, Alpharetta, GA 30022, <http://www.crcac.org>.