



Designation: E2952 – 23

Standard Specification for Air-Purifying Respiratory Protective Smoke Escape Devices (RPED)¹

This standard is issued under the fixed designation E2952; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This specification covers the minimum requirements for the design, performance, testing, and certification of air-purifying respiratory protective smoke escape devices for immediate emergency evacuation without entry/re-entry.

1.2 The purpose of this specification shall be to provide minimum requirements for respiratory protective escape devices that provide limited protection for 15 min for escape from the by-products of fire, including particulate matter, carbon monoxide, other toxic gases, and the effects of radiant heat.

1.3 The requirements of this specification specify an air-purifying respiratory protective escape device with a laboratory-tested 15-min service life intended to provide head, eye, and respiratory protection from particulate matter, irritants, and toxic gases and vapors commonly produced by fire.

1.4 Controlled laboratory tests that are used to determine compliance with the performance requirements of this specification shall not be deemed as establishing performance levels for all situations to which individuals can be exposed.

1.5 This specification shall not apply to the requirements for provision, installation, or use of air-purifying respiratory protective smoke escape devices.

1.6 This specification shall not apply to respiratory protective escape devices intended for use in circumstances in which an oxygen deficiency (oxygen less than 19.5 % by volume) exists or might exist.

1.7 This specification is not intended to be used as a detailed manufacturing or purchase specification, but shall be permitted to be referenced as a minimum requirement in purchase specifications.

1.8 The conformity assessment requirements of Guide **F3050**, Model C, shall apply to the certification of products in accordance with this specification.

¹ This specification is under the jurisdiction of ASTM Committee **E54** on Homeland Security Applications and is the direct responsibility of Subcommittee **E54.04** on Public Safety Equipment.

Current edition approved May 1, 2023. Published June 2023. Originally approved in 2014. Last previous edition approved in 2022 as E2952 – 22. DOI: 10.1520/E2952-23.

1.9 *Units*—The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.

1.10 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.*

1.11 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

2. Referenced Documents

2.1 ASTM Standards:²

D1003 Test Method for Haze and Luminous Transmittance of Transparent Plastics

D4101 Classification System and Basis for Specification for Polypropylene Injection and Extrusion Materials

F1140 Test Methods for Internal Pressurization Failure Resistance of Unrestrained Packages

F3050 Guide for Conformity Assessment of Personal Protective Clothing and Equipment

F3387 Practice for Respiratory Protection

2.2 CEN Standard:³

EN 136 Respiratory protective devices - Full face masks - Requirements, testing, marking

2.3 ISO Standards:⁴

ISO/IEC 17065 Conformity Assessment—Requirements for Bodies Certifying Products, Processes and Services

ISO 9001 Quality Systems—Model for Quality Assurance in

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

³ Available from European Committee for Standardization (CEN), Avenue Marnix 17, B-1000, Brussels, Belgium, <http://www.cen.eu>.

⁴ Available from International Organization for Standardization (ISO), 1, ch. de la Voie-Creuse, CP 56, CH-1211 Geneva 20, Switzerland, <http://www.iso.org>.

Design, Development, Production, Installation, and Servicing

ISO 9002 Quality Systems—Model for Quality Assurance in Production, Installation, and Servicing.

2.4 **NFPA Standard:**⁵

NFPA 1981 Standard on Open-Circuit Self-Contained Breathing Apparatus for the Fire Service

2.5 **NIOSH Procedures:**⁶

NIOSH CET-APRS-STP-CBRN-0411, Rev 1.1 Laboratory Durability Conditioning Process for Environmental, Transportation and Rough Handling Use Conditions on Chemical, Biological, Radiological and Nuclear (CBRN) (AirPurifying or Self-Contained) Escape Respirator

3. Terminology

3.1 Definitions:

3.1.1 *air-purifying respiratory protective smoke escape device, RPED, n*—air-purifying respirator used to protect a person while escaping from a fire by removing certain contaminants of fire-generated products of combustion from the inhaled air.

3.1.2 *accessory, n*—item that may be provided with an RPED that does not affect its ability to meet the requirements of this specification.

3.1.3 *approved, adj*—acceptable to the authority having jurisdiction.

3.1.4 *authority having jurisdiction, n*—organization, office, or individual responsible for approving any equipment, an installation, or a procedure.

3.1.5 *basic plane, n*—plane through the centers of the external ear openings and the lower edges of the eye sockets.

3.1.6 *canister (air purifying), n*—container with (1) gas and vapor-removing sorbent or catalyst, or (2) gas- and vapor-removing sorbent or catalyst that removes gases and vapors and filter that removes particles from inspired air (or air drawn through the unit).

F3387

3.1.7 *certification/certify, n/adj*—system whereby an organization determines that a manufacturer has demonstrated the ability to produce a product that complies with the requirements of this specification, authorizes the manufacturer to use a label on listed products that comply with the requirements of this specification, and establishes a follow-up program conducted by the organization as a check on the methods the manufacturer uses to determine continued compliance of labeled and listed products with the requirements of this specification.

3.1.8 *certification organization, n*—independent third-party organization that determines product compliance with the requirements of this specification with a labeling/listing/follow-up program.

3.1.9 *compliance/compliant, n/adj*—meeting or exceeding all applicable requirements of this specification.

3.1.10 *donning time, n*—time for equipment in hand to be placed over the head of the wearer and become functional. This time shall include the removal of an operational packaging.

3.1.11 *follow-up program, n*—sampling, inspections, tests, or other measures conducted by the certification organization on a periodic basis to determine the continued compliance of listed products that are being produced by the manufacturer to the requirements of this specification.

3.1.12 *gas, n*—fluid that has neither independent shape nor volume and tends to expand indefinitely.

3.1.13 *haze, n*—percent of incident light that is not transmitted in a straight line through the lens but forward scattered, greater than 2.5° diverging.

3.1.14 *identical respiratory protective escape device, n*—RPED that is produced to the same engineering and manufacturing specifications.

3.1.15 *labeled, adj*—equipment or material to which has been attached a label, symbol, or other identifying mark of an organization that is acceptable to the authority having jurisdiction and concerned with product evaluation, that maintains periodic inspection of production of labeled equipment or materials, and by whose labeling the manufacturer indicates compliance with appropriate standards or performance in a specified manner.

3.1.16 *light transmission, n*—ratio of the luminous (approximately 380- through 760-mm) radiant power transmitted by an object to the incident luminous radiant power.

3.1.17 *listed, adj*—equipment, materials, or services included in a list published by the certification organization.

3.1.18 *melt, v*—to change from solid to liquid or become consumed by action of heat in a manner that could injure the user.

3.1.19 *model, n*—term used to identify an RPED, including all variants to its design.

3.1.20 *product label, n*—marking affixed to the RPED by the manufacturer containing general information, warnings, care, maintenance, or similar data.

3.1.20.1 *Discussion*—This product label is not the certification organization's label, symbol, or identifying mark; however, the certification organization's label, symbol, or identifying mark may be attached to it or be part of it. **See labeled.**

3.1.21 *ready-to-use configuration, n*—RPED in its final packaging state before use that, upon opening or removing this operational package, allows the user to don the RPED within the required donning time.

3.1.22 *RPED, n*—a “short hand” acronym for Air-Purifying Respiratory Protective Smoke Escape Device.

3.1.23 *service life, n*—the manufacturer-declared duration of protection provided by the RPED for escape once the operational packaging is opened or removed from an RPED in a ready-to-use configuration.

3.1.24 *shall, v*—indicates a mandatory requirement.

⁵ Available from National Fire Protection Association (NFPA), 1 Batterymarch Park, Quincy, MA 02169-7471, <http://www.nfpa.org>.

⁶ Available from Centers for Disease Control and Prevention (CDC), 1600 Clifton Rd., Atlanta, GA 30329-4027, <http://www.cdc.gov>.