



Standard Specification for Heat Sanitizing Commercial Pot, Pan, and Utensil Washing Machines, Stationary Rack, Water-Driven Rotary Spray Type¹

This standard is issued under the fixed designation F1114; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This specification covers manually fed, spray-type stationary rack, automatically controlled, water-driven rotary spray commercial pot, pan, and utensil washing machines, herein referred to as “the washer.”

1.2 The values stated in inch-pound units are to be regarded as standard. The values given in parentheses are mathematical conversions to SI units that are provided for information only and are not considered standard.

1.3 The following safety hazards caveat pertains only to the test methods portion, Section 9, of this specification. *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.*

1.4 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

2. Referenced Documents

2.1 ASTM Standards:²

- A240/A240M Specification for Chromium and Chromium-Nickel Stainless Steel Plate, Sheet, and Strip for Pressure Vessels and for General Applications
- A276 Specification for Stainless Steel Bars and Shapes
- A436 Specification for Austenitic Gray Iron Castings

¹ This specification is under the jurisdiction of ASTM Committee F26 on Food Service Equipment and is the direct responsibility of Subcommittee F26.01 on Cleaning and Sanitation Equipment.

Current edition approved April 1, 2022. Published April 2022. Originally approved in 1988. Last previous edition approved in 2016 as F1114 – 16. DOI: 10.1520/F1114-22.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

A554 Specification for Welded Stainless Steel Mechanical Tubing

A582/A582M Specification for Free-Machining Stainless Steel Bars

B127 Specification for Nickel-Copper Alloy Plate, Sheet, and Strip

D3951 Practice for Commercial Packaging

F760 Specification for Food Service Equipment Manuals

F1021 Specification for Feeders, Detergent, Rinse Agent, and Sanitizing Agent for Commercial Dishwashing and Glasswashing Machines

F1696 Test Method for Energy Performance of Stationary-Rack, Door-Type Commercial Dishwashing Machines

2.2 Federal Regulation:³

29 CFR Part 1910 OSHA Regulations on Safety

2.3 NSF International Standards:⁴

NSF/ANSI 3 Commercial Warewashing Equipment

NSF/ANSI 5 Commercial Hot Water Generating Equipment

NSF/ANSI 29 Detergent/Chemical Feeders for Commercial Spray-Type Dishwashing Machines

NSF Listings—Food Equipment

2.4 Underwriters Laboratories Standard:⁵

UL 921 Commercial Dishwashers

3. Terminology

3.1 Definitions of Terms Specific to This Standard:

3.1.1 *commercial pot, pan, and utensil washing machines*—machines that uniformly wash, rinse, and heat-sanitize food preparation utensils. The machines are capable of removing physical soil from properly racked and pre-scrapped items, and sanitizing multiple pots, pans, and utensils.

4. Classification

4.1 *General*—The washers shall be of the types, styles, sizes, and classes specified as follows:

³ Available from U.S. Government Printing Office Superintendent of Documents, 732 N. Capitol St., NW, Mail Stop: SDE, Washington, DC 20401.

⁴ Available from NSF International, P.O. Box 130140, 789 N. Dixboro Rd., Ann Arbor, MI 48113-0140.

⁵ Available from Underwriters Laboratories (UL), 333 Pfingsten Rd., Northbrook, IL 60062.

4.2 Types:

4.2.1 *Type I*—One rack (up to a nominal capacity of 25 racks/h).

4.2.1.1 *Style A*—Two doors (pass-through).

4.2.1.2 *Style B*—One door (front-loading).

4.2.1.3 *Style C*—One or two doors (corner).

4.2.1.4 *Style D*—Three doors (pass-through with front clean-out door).

4.2.2 *Type II*—Two rack (up to a nominal capacity of 46 racks/h).

4.2.2.1 *Style A*—Two doors (pass-through).

4.2.2.2 *Style B*—Three doors (pass-through with clean-out).

4.3 Classes:

4.3.1 *Class 1*—Steam heated.

4.3.1.1 *Mode A*—Injector.

4.3.1.2 *Mode B*—Heat exchange coil.

4.3.2 *Class 2*—Electric heat.

4.3.3 *Class 3*—Gas heat.

4.3.3.1 Natural gas.

4.3.3.2 LP gas.

5. Ordering Information

5.1 Purchasers should select the preferred options permitted in this specification and include in the procurement document the following information:

5.1.1 Title, designation, and date of this specification.

5.1.2 Type, style, class, and mode of machine required (see Section 4).

5.1.3 Noise level requirements, if other than specified (see 8.2).

5.1.4 Whether a service-supply valve is required (see 7.5).

5.1.5 When a standard 40°F (22°C) temperature rise steam or electric booster is required. If the required temperature rise is more than 40°F (22°C) (see 7.14), it should be specified.

5.1.6 Electrical power supply characteristics (current, voltage, phase, frequency).

5.1.7 Whether a detergent feeder is required (see 7.15).

5.1.8 Accessory equipment, spare, and maintenance parts required, and selected options.

5.1.9 Treatment and painting if other than specified (see 7.18).

5.1.10 When energy consumption profiles, water consumption profiles, or productivity profiles are desired (see 9.3).

5.1.11 Manufacturer's certification, when required (see Section 10).

6. Materials

6.1 All materials shall be specified as follows:

6.1.1 Materials used shall be free from defects that would adversely affect the performance or maintainability of individual components of the overall assembly. The machines shall meet the material requirements of NSF/ANSI 3 where applicable.

6.1.2 *Corrosion-Resistant Steel*—Corrosion-resisting steel shall conform to the requirements of any 300 series stainless steel specified in Specifications A240/A240M, A276, A554, and A582/A582M.

6.1.3 *Corrosion-Resistant Material*—Corrosion-resisting material is material other than corrosion-resistant steel that is equivalent to use in the washer application.

6.1.4 *Nickel-Copper Alloy*—Nickel-copper alloys shall conform to the requirements of Specification B127.

7. Design and Construction

7.1 The machines shall meet the design and construction requirements for NSF/ANSI 3 where applicable.

7.2 The washing machines shall be complete so that when connected to the specified source of power, water supply, heating means (steam or electric), drainage and detergent feeder, as applicable, the unit can be used for its intended function. Machines shall be rigid and quiet in operation (see 8.2). Parts requiring adjustment or service, or both, shall be readily accessible. The machine shall wash pots, pans, and utensils by means of a water and detergent solution pumped from a tank, and shall final rinse the pots, pans, and utensils with fresh water from an outside source. Provisions shall be made to fill the wash tank either directly from the regular hot water supply with a hand valve or through the booster or solenoid, or both. The wash, dwell, and rinse cycles shall be automatically controlled. A light shall be provided to indicate when the machine is in operation. Machines shall be provided with tracks of corrosion-resistant steel not less than 0.070-in. (0.178-cm) thick or with other equivalent corrosion-resisting material. They shall have an inside working height, including the door height of not less than 27 in. (686 mm) above the track.

7.3 *Piping, Tubing Fittings, and Valves (Installation)*—Connections shall be readily accessible to facilitate installation and maintenance. Piping, tubing, and valves shall be located, whenever possible, on the exterior of the machine.

7.4 *Piping and Fittings*—Water, steam piping, and fittings shall be of corrosion-resisting material. Fresh water supply to the tank shall be discharged not lower than 2 in. (5.08 cm) above the maximum flood level rim, or an effective air gap or vacuum breaker shall be installed to prevent backflow in accordance with NSF/ANSI 3. The drain and other plumbing connections shall be standard pipe or tubing connections. Drainage piping shall be corrosion-resisting material, or suitable heat-resisting plastic material. Drains may be joined into a single trunk line requiring only one connection or arranged to permit individual connections to the waste line.

7.5 *Valves*—Steam valves shall be corrosion-resisting material designed for steam applications and for a saturated steam working pressure of 50 psi (344.6 kPa). When specified (see 5.1.4), a separately packed service supply valve shall be provided for closing the supply of water to the machine. A suitable closure or drain valve shall be furnished when not supplied with a pumped drain system. A permanent identification on the machine shall show “open” and “closed” positions on the manual drain. Fresh water rinse valves shall be reliable, fully automatic, and suitable for 210°F (98.9°C) water. The manually operated valves, when used, shall be identified.

7.6 *Spray Assemblies*—All spray nozzles and spray arm manifolds shall be of corrosion-resisting materials. All spray