



Designation: F1410 – 98 (Reapproved 2022)

Standard Test Method for Measuring Maximum Functional Wet Volume of Utility Vacuum Cleaners¹

This standard is issued under the fixed designation F1410; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This test method is applicable to any vacuum cleaner that is classified as a utility vac.

1.2 The values stated in inch-pound units are to be regarded as standard. The values given in parentheses are for information only.

1.3 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.*

1.4 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

2. Significance and Use

2.1 This test method covers a procedure to determine the maximum functional wet volume that the utility vac is capable of collecting.

3. Apparatus

3.1 *Voltmeter*, to measure input to the cleaner, providing measurements accurate to within ± 1 %.

3.2 *Voltage Regulator System*—The regulator shall be capable of maintaining the rated voltage (± 1 %) and frequency (± 1 Hz) with sinusoidal wave form.

3.3 *Temperature and Relative Humidity Indicators*, to provide temperature measurements accurate to within ± 1 °F ($\pm \frac{1}{2}$ °C) and humidity measurements accurate to within ± 2 % relative humidity.

3.4 *Weighing Scale*—The scale shall be accurate to 1 % of full scale and have a weighing capacity of at least 250 lb (113.4 kg).

¹ This test method is under the jurisdiction of ASTM Committee F11 on Vacuum Cleaners and is the direct responsibility of Subcommittee F11.23 on Filtration.

Current edition approved Aug. 1, 2022. Published August 2022. Originally approved in 1992. Last previous edition approved in 2016 as F1410 – 98 (2016). DOI: 10.1520/F1410-98R22.

4. Materials

4.1 *Water*.

5. Sampling

5.1 Test a sample of each basic model until a 90 % confidence level (about the mean) is established within ± 5 % of the mean value. Test a minimum of three samples. Select all samples at random in accordance with good statistical practice.

NOTE 1—See [Appendix X1](#) for method of determining 90 % confidence level.

6. Conditioning

6.1 *Test Room*—The test room should be maintained at 70 °F $\pm$ 5 °F (21 °C $\pm$ 3 °C) and 45 % to 55 % relative humidity.

7. Procedure

7.1 Equip the vac with a new filter.

7.2 Weigh the empty vac including the power supply cord. (Do not include the hose or any accessories.)

7.3 Unit must be on a level surface and the shut-off device must be in place if the unit is designed to be used with one.

7.4 Level of the water to be picked up shall be lower than the floor level of vac such that no siphoning occurs.

7.5 Tests are to be conducted at the nameplate voltage (± 1 %) and frequency (± 1 Hz), when measured at the appliance plug. For cleaners with dual nameplate voltage ratings, conduct tests at the highest voltage.

7.6 Using the largest hose supplied with the unit, vacuum water into the vac-tank. Maintain a water pick up rate of 2 gal/min throughout the filling cycle.

7.7 Collect water with the vac until either one of the following occurs:

7.7.1 The unit stops collecting water, or

7.7.2 Water overflows from the vac.

7.8 Stop unit and disconnect hose from the vac. Any water remaining in the hose shall not be included in the maximum functional volume.

7.9 Weigh the filled vac, including the power supply cord.

7.10 Calculate the maximum functional volume by dividing the weight of the water collected by the weight per gallon of water as follows:

$$\text{volume, gal} = \frac{\text{weight (lb) vac filled} - \text{weight (lb) vac empty}}{8.328 \text{ lb/gal}}$$

7.11 Record the maximum functional wet volume in gallons (litres) to the nearest tenth.

7.12 Repeat steps 7.1 through 7.12 two more times. The average of the three tests represents the maximum wet functional volume that the utility vac is capable of collecting.

8. Precision and Bias²

8.1 *Precision*—These statements are based on an interlaboratory test involving six laboratories and four units. The range of maximum functional volume of the units was from 3.8 gal to 13.5 gal.

8.1.1 *Repeatability (Single-Operator-Laboratory, Multiday)*:

8.1.1.1 Repeatability for wet volume values of 5 gal and under, within a laboratory divided by the average (coefficient of variation) was found to be 4.5 % or less. Two values from a sample of three should be considered suspect (at the 95 % confidence level) if they differ by more than 12.8 %.

² Supporting data have been filed at ASTM International Headquarters and may be obtained by requesting Research Report RR:F11-1009. Contact ASTM Customer Service at service@astm.org.

NOTE 2—The percent difference = (larger – smaller)/(larger) × 100.

8.1.1.2 Repeatability for wet volume values of over 5 gal, the standard deviation within a laboratory divided by the average (coefficient of variation) was found to be 2.5 % or less. Two values from a sample of three should be considered suspect (at the 95 % confidence level) if they differ by more than 7.1 %.

NOTE 3—The percent difference = (larger – smaller)/(larger) × 100.

8.1.2 *Reproducibility (Multilaboratory, Multiday)*:

8.1.2.1 Reproducibility for wet volume values of 5 gal and under, the standard deviation divided by the average (coefficient of variation) with a single unit tested in different laboratories was found to be 10.7 % or less. Two such values should be considered suspect (at the 95 % confidence level) if they differ by more than 33 %.

8.1.2.2 Reproducibility for wet volume values over 5 gal, the standard deviation divided by the average (coefficient of variation) with a single unit tested in different laboratories was found to be 3.2 % or less. Two such values should be considered suspect (at the 95 % confidence level) if they differ by more than 11.5 %.

8.2 *Bias*—No justifiable statement can be made on the bias of this test method for the properties listed. The true values of the properties cannot be established by acceptable referee methods.

9. Keywords

9.1 utility vacuum cleaner; wet volume

APPENDIX

(Nonmandatory Information)

X1. DETERMINATION OF 90 % CONFIDENCE INTERVAL

X1.1 The most common and ordinarily the best single estimate of the population mean μ is simply the arithmetic mean of the measurements. When a sample is taken from a population, the sample average will seldom be exactly the same as the population average; however, it is hoped to be fairly close so that the statement of confidence interval will bracket the true mean.

X1.2 The following procedure gives an interval which is expected to bracket μ , the true mean, $100(1 - \alpha)$ % of the time. This provides a $100(1 - \alpha)$ % confidence level. α is the chance of being wrong, therefore, $1 - \alpha$ is the probability of being correct.

X1.2.1 Choose the desired confidence level, $1 - \alpha$.

X1.2.2 Compute Mean ($\bar{X}$):

$$\bar{X} = \frac{1}{n} \sum_{i=1}^n X_i$$

$$\text{Standard Deviation, } s = \sqrt{\frac{n \sum X_i^2 - (\sum X_i)^2}{n(n-1)}}$$

where:

n = number of units.

X1.2.3 Compute the upper limit (X_μ) and the lower limit (X_L):

$$X_\mu = \bar{X} + ts/\sqrt{n}$$

$$X_L = \bar{X} - ts/n$$

where:

t = value from Table X1.1 at $(1 - \alpha)/2$.

X1.3 The interval from X_L to X_μ is a $100(1 - \alpha)$ % confidence interval for the population mean; that is, we may assert with $100(1 - \alpha)$ % confidence that $X_L < \mu < X_\mu$. It can be seen that as $n \rightarrow \infty$, $ts/\sqrt{n} \rightarrow 0$. Thus, a smaller confidence interval for the mean can be obtained by using larger samples. In