



Designation: F2067 – 22

Standard Practice for Development and Use of Oil-Spill Trajectory Models¹

This standard is issued under the fixed designation F2067; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reappraisal. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reappraisal.

1. Scope

1.1 This practice describes the features and processes that should be included in an oil-spill trajectory and fate model.

1.2 This practice applies only to oil-spill models and does not consider the broader need for models in other fields. This practice considers only computer-based models, and not physical modeling of oil-spill processes.

1.3 This practice is applicable to all types of oil in oceans, lakes, and rivers under a variety of environmental and geographical conditions.

1.4 This practice applies primarily to two-dimensional models. Consideration is given to three-dimensional models for complex flow regimes.

1.5 The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.

1.6 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

2. Terminology

2.1 Definitions:

2.1.1 *trajectory model*—a computer-based program that predicts the motion and fate of oil on water as a function of time.

2.1.1.1 *Discussion*—Input parameters include oil properties, weather, and oceanographic information. There are four different modes: forecast, hindcast, stochastic, and receptor.

2.1.2 *contingency planning*—planning of several types to prepare for oil spills.

2.1.2.1 *Discussion*—This planning can include modeling such as described in this guide, to predict where oil spills might go and what the fate and properties of that oil would be.

¹ This practice is under the jurisdiction of ASTM Committee F20 on Hazardous Substances and Oil Spill Response and is the direct responsibility of Subcommittee F20.16 on Surveillance and Tracking.

Current edition approved Nov. 1, 2022. Published December 2022. Originally approved in 2000. Last previous edition approved in 2019 as F2067 – 19. DOI: 10.1520/F2067–22.

3. Significance and Use

3.1 Trajectory models are used to predict the future movement and fate of oil (forecast mode) in contingency planning, in exercises and during real spill events. This information is used for planning purposes to position equipment and response personnel in order to optimize a spill response. Oil-spill trajectory models are used in the development of scenarios for training and exercises. The use of models allows the scenario designer to develop incidents and situations in a realistic manner.

3.2 Oil-spill trajectory models can be used in a statistical manner (stochastic mode) to identify the areas that may be impacted by oil spills.

3.3 In those cases where the degree of risk at various locations from an unknown source is needed, trajectory models can be used in an inverse mode to identify the sources of the pollution (hindcast mode).

3.4 Models can also be used to examine habitats, shorelines, or areas to predict if they would be hit with oil from a given source (receptor mode).

4. Modelling Methods

4.1 Models simulate the movement of oil on water, calculates the various weathering processes and considers the interaction of the oil with the shoreline. The input data needed by the model includes area maps, oil properties, and spatial and temporal vectors of wind and ocean currents. In some models, there are separate programs for advection and fate. In some cases, the fate models calculate weathering on the total mass of the oil rather than on individual particles. Some models include response strategies (skimming, burning, dispersing, and so forth) and the effect of these on the mass balance.

4.2 The computer model calculates the surface fate of the oil using physical and chemical properties of the oil and weathering algorithms.

4.3 The output of a model is a map showing oil-slick locations as a function of time, and graphs and tables of the weathering of the oil and mass balance.

4.4 The output of the model is subject to uncertainties, primarily caused by uncertainties in the input data from forecast winds and predicted ocean currents. The model should include an estimate of the magnitude of these uncertainties. It