



Designation: F3084 – 23

## Standard Consumer Safety Specification for Infant and Infant/Toddler Rockers<sup>1</sup>

This standard is issued under the fixed designation F3084; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reappraisal. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reappraisal.

### INTRODUCTION

This consumer safety specification addresses incidents associated with infant and infant/toddler rockers identified by the U.S. Consumer Product Safety Commission (CPSC).

In response to incident data compiled by the CPSC, this specification attempts to minimize the following hazards: disassembly/collapse, stability, and falls from elevated surfaces.

This specification is intended to cover normal use and reasonably foreseeable misuse or abuse of the product(s).

This specification is written within the current state-of-the-art of product technology and will be updated whenever substantive information becomes available that necessitates additional requirements or justifies the revision of existing requirements.

### 1. Scope

1.1 This consumer safety specification covers establishment of requirements, test methods, and marking requirements to promote safe use of the rocker by an occupant and a caregiver.

1.2 This specification does not cover rockers intended for toddler only use without a restraint system, hand-held infant carriers, or sleep products that have the ability to rock or have a rocking mode.

1.3 This consumer safety specification is intended to minimize the risk of injury to an occupant resulting from normal use and reasonably foreseeable misuse or abuse of an infant or infant/toddler rocker.

1.4 No rocker produced after the approval date of this consumer safety specification shall, either by label or other means, indicate compliance with this specification unless it conforms to all requirements contained herein.

1.5 This consumer safety specification is not intended to address incidents and injuries resulting from the interaction of other persons with the occupant in the product or the incidents resulting from abuse or misuse by other children.

1.6 The values stated in inch-pound units are to be regarded as standard. The values given in parentheses are mathematical conversions to SI units that are provided for information only and are not considered standard.

<sup>1</sup> This consumer safety specification is under the jurisdiction of ASTM Committee F15 on Consumer Products and is the direct responsibility of Subcommittee F15.21 on Infant Carriers, Bouncers and Baby Swings.

Current edition approved Dec. 1, 2023. Published January 2024. Originally approved in 2014. Last previous edition approved in 2022 as F3084 – 22. DOI: 10.1520/F3084-23.

1.7 The following precautionary caveat pertains only to the test methods portion, Section 7, of this specification: *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.*

1.8 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

### 2. Referenced Documents

#### 2.1 ASTM Standards:<sup>2</sup>

D3359 Test Methods for Rating Adhesion by Tape Test

F963 Consumer Safety Specification for Toy Safety

F2050 Consumer Safety Specification for Hand-Held Infant Carriers

F2167 Consumer Safety Specification for Infant Bouncer Seats

F2194 Consumer Safety Specification for Bassinets and Cradles

#### 2.2 EN Standards:

EN 12790:2009 Child use and care articles—Reclined cradles

<sup>2</sup> For referenced ASTM standards, visit the ASTM website, [www.astm.org](http://www.astm.org), or contact ASTM Customer Service at [service@astm.org](mailto:service@astm.org). For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

### 2.3 Federal Regulations:

**16 CFR 1303** Ban of Lead-Containing Paint and Certain Consumer Products Bearing Lead-Containing Paint

**16 CFR 1500.48** Technical Requirements for Determining a Sharp Point in Toys or Other Articles Intended for Use by Children Under Eight Years of Age

**16 CFR 1500.49** Technical Requirements for Determining a Sharp Metal or Glass Edge in Toys or Other Articles Intended for Use by Children Under Eight Years of Age

**16 CFR 1500.50-.52** Test Methods for Simulating Use and Abuse of Toys and Other Articles Intended for Use by Children

**16 CFR 1501** Method for Identifying Toys and Other Articles Intended for Use by Children Under Three Years of Age Which Present Choking, Aspiration or Ingestion Hazards Because of Small Parts

### 2.4 ANSI Standards:<sup>3</sup>

**ANSI Z535.1** Safety Colors

**ANSI Z535.4** Product Safety Signs and Labels

**ANSI Z535.6** Product Safety Information in Product Manuals, Instructions, and Other Collateral Materials

### 2.5 Other References:

**49 CFR Part 572.25** NHTSA Subpart D—6 Month-Old CAMI Infant Dummy, Mark II, Fig. 1

**49 CFR Part 572.90 and 572.91** NHTSA Subpart K—CAMI Newborn Infant Dummy, Fig. 2

## 3. Terminology

### 3.1 Definitions:

**3.1.1 conspicuous**, *adj*—visible, when the product is in a manufacturer's recommended use position, to a person sitting near the product at any one position around the product but is not necessarily visible from all positions.

**3.1.2 double-action release system**, *n*—a mechanism requiring either two consecutive actions, the first of which must be maintained while the second is carried out, or two separate and independent simultaneous actions to fully release.

**3.1.3 dynamic load**, *n*—application of an impulsive force through free fall of a weight.

**3.1.4 fabric**, *n*—any woven, knit, coated, laminated, extruded, or calendered flexible material that is intended to be sewn, welded, heat sealed, or glued together as an assembly.

**3.1.5 grasping point on toy bar**, *n*—five-inch wide section of the toy bar centered at the mid-point of the toy bar if the toy bar is attached at two points on the frame.

**3.1.5.1 Discussion**—If the toy bar has a single attachment point, the 5-in. dimension is either centered at the mid-point of the product or as close to the mid-point as possible, should the toy bar not extend far enough beyond the mid-point to achieve this. The load should be evenly distributed over this 5-in. dimension.

**3.1.6 infant rocker**, *n*—a freestanding product intended to support an occupant who has not developed the ability to sit up unassisted, weighing up to 20 lb, (approximately 0 to 6 months

of age) in a seated, reclined position greater than 10° and to facilitate rocking by the occupant with the aid of the caregiver or by other means.

**3.1.7 infant/toddler rocker**, *n*—a freestanding product intended to support an occupant in a seated, reclined position greater than 10° and to facilitate rocking by the occupant with the aid of the caregiver or by other means until the occupant is approximately 2½ years, weighing up to 40 lb.

**3.1.7.1 Discussion**—Infant/toddler rockers may also include products that transition from an infant rocker to a toddler rocker and that can be used without a restraint system for independent rocking by child that can climb in and out of the product unassisted.

**3.1.8 kickstand**, *n*—a device intended by the manufacturer to prevent any rocking motion.

**3.1.8.1 Discussion**—A kickstand may include hinged legs, feet or other mechanical stops.

**3.1.9 manufacturer's recommended use position(s)**, *n*—any position that is presented as a normal, allowable, or acceptable configuration for the use of the product by the manufacturer in any descriptive or instructional literature.

**3.1.9.1 Discussion**—This specifically excludes positions that the manufacturer shows in a like manner in its literature to be unacceptable, unsafe, or not recommended.

**3.1.10 non-paper label**, *n*—any label material (such as plastic or metal) that either will not tear without the aid of tools or tears leaving a sharply defined edge.

**3.1.11 occupant**, *n*—that individual who is in a product that is set up in one of the manufacturer's recommended use positions.

**3.1.12 paper label**, *n*—any label material that tears without the aid of tools and leaves a fibrous edge.

**3.1.13 protective component**, *n*—any component used for protection from sharp edges, points, or entrapment of fingers or toes.

**3.1.13.1 Discussion**—Examples of protective components include caps, sleeves and plugs.

**3.1.14 seam**, *n*—means of joining fabric components, such as sewing, welding, heat sealing, or gluing.

**3.1.15 seat bight**, *n*—the intersection of the seat back surface with the seat bottom surface (see Figs. 3 and 4).

**3.1.16 static load**, *n*—vertically downward load applied by weights or other means.

**3.1.17 toy bars**, *n*—any bar or mobile connected to the frame of the product in any location with one or more attachment points typically used to suspend toys over the occupant.

**3.1.17.1 Discussion**—Canopies, fixed and rotating, are not considered a toy bar regardless of whether they allow for the attachment of toys.

## 4. Calibration and Standardization

**4.1** All testing shall be conducted on a concrete floor, which may be covered with ⅛-in. (3-mm) thick vinyl flooring cover, unless the test instructs differently.

<sup>3</sup> Available from American National Standards Institute (ANSI), 25 W. 43rd St., 4th Floor, New York, NY 10036, <http://www.ansi.org>.