



© British Standards Institution. No part of this publication may be photocopied or otherwise reproduced without the prior permission in writing of BSI.

British Standard

Hexagon socket screws and wrench keys: metric series

Part 7. Specification for hexagon socket shoulder screws

Vis à six pans creux et clés mâles pour six pans: série métrique

Partie 7. Vis ajustables à six pans creux et à bout fileté réduit — Spécifications

Innensechskantschrauben und Steckschlüssel: metrische Reihe

Teil 7. Innensechskantschrauben mit Zapfen

Contents

	Page
Foreword	Inside front cover
Cooperating organizations	Back cover

Specification

1. Scope	1
2. References	1
3. Dimensions and surface detail	1
4. Tolerances of form and position	4
5. Specifications and reference standards	5
6. Designation	5

Tables

1. Dimensions	3
2. Specifications and reference standards	5

Figures

1. Shoulder screws	2
2. Tolerances of form and position	4

Compliance with a British Standard does not of itself confer immunity from legal obligations.

Foreword

This British Standard has been prepared under the direction of the Mechanical Engineering Standards Committee and forms part of the revision of BS 4168 : 1967. It is one of a series of specifications, of which the full list is as follows.

- Part 1. Specification for hexagon socket head cap screws
- Part 2. Specification for hexagon socket set screws with flat point
- Part 3. Specification for hexagon socket set screws with cone point
- Part 4. Specification for hexagon socket set screws with dog point
- Part 5. Specification for hexagon socket set screws with cup point
- Part 6. Specification for hexagon socket button head screws
- Part 7. Specification for hexagon socket shoulder screws
- Part 8. Specification for hexagon socket countersunk head screws
- Part 9.* Specification for wrench keys

This Part of this standard is based on a draft standard prepared by ISO/TC 2 'Fasteners'. It differs from the ISO/TC 2 draft in that note has been taken of European and United Kingdom market requirements and that shoulder sizes 6 mm, 12 mm and 24 mm are specified in place of shoulder sizes 6.5 mm, 13 mm and 25 mm.

If, in special cases, requirements other than those listed in this standard are necessary, it is recommended that they should be selected from the standards referred to in clause 5.



*In course of preparation.