

(2)

97年08月 22

1986年 3月 1日 上午 9时 10分 98年7月 5

2000年9月28日

99年7月30


Specification for

Hermetically sealed flat double glazing units

Spécification pour fenêtres plates à double vitrage étanche

Spezifikation für hermetisch abgedichtete flache Doppelverglasungseinheiten

2000年6月2日



1980年十月三十日

Contents

	Page		Page
Foreword	Inside front cover	Tables	
Cooperating organizations	Back cover	1. Typical thermal transmittances for different conditions of exposure	1
Specification		2. Size limitations for production units covered by this standard	11
1. Scope	1	Figures	
2. References	1	1. Typical example of a viewing box for ultraviolet exposure test	5
3. Definitions	1	2. Typical example of a jig and dial gauge for measuring change in thickness	6
4. Materials	1	3. Typical example of apparatus for dew-point measurement	6
5. Dimensions	1	4. Typical example of ultraviolet fogging test apparatus	7
6. Dimensional tolerances	2	5. Typical example of weathering apparatus for sealed double glazing units	8
7. Marking description	2	6. Typical example of a high humidity cycling cabinet	10
8. Performance	2		
Appendices			
A. Methods of test	3		
B. Performance	11		

Foreword

This British Standard has been prepared under the direction of the Elements and Components for Buildings Standards Committee. It covers factory made hermetically sealed flat double glazing units used for insulation in building. These units are intended to be glazed in accordance with CP 152.

Compliance with the tests is an assurance to the purchaser and the customer that the seal of units, manufactured to the same design and under similar conditions, will fulfil the performance requirements specified in this standard.

The sample testing specified in the appendices is designed to reflect the performance, in service, of symmetrical and asymmetrical units manufactured by the techniques employed in routine production.

The detail design of units is not covered by this standard, this being a matter for individual manufacturers.

Certification. Attention is drawn to the certification facilities described on the inside back cover of this standard.