



BS 6431 : Part 3 : Section 3.2 : 1986
EN 186-2

UDC 691.433-413-033.6:666.75-184.2

© British Standards Institution. No part of this publication may be photocopied or otherwise reproduced without the prior permission in writing of BSI

British Standard

Ceramic floor and wall tiles

Part 3. Extruded ceramic tiles with a water absorption of
 $3\% < E \leq 6\%$

Group Alla. Section 3.2 Specification for specific products
(terre cuite, cotto, baldosin catalan)

Carreaux et dalles céramiques pour sols et murs

Partie 3. Carreaux et dalles céramiques étirés à absorption d'eau $3\% < E \leq 6\%$.

Groupe Alla. Section 3.2

Keramische Fliesen und Platten für Bodenbeläge und Wandbekleidungen

Teil 3. Stranggepreßte keramische Fliesen und Platten mit einer Wasseraufnahme von $3\% < E \leq 6\%$.

Gruppe Alla. Abschnitt 3.2

The European Standard EN 186-2 has the status of a British Standard.

British Standards Institution

BS 6431 : Part 3 : Section 3.2 : 1986

Contents

	Page		Page
National foreword	Inside front cover	Tables	
Brief history	2	1 Modular preferred sizes for split tiles	4
National appendix A	Inside back cover	2 Non-modular sizes for split tiles	4
National appendix B	Inside back cover	3 Modular preferred sizes for quarry tiles	5
Cooperating organizations	Back cover	4 Non-modular sizes for quarry tiles	5
		5 <i>(Requirements)*</i>	6
Specification		Figures	
1 Scope and field of application	3	1 Split tile	3
2 References	3	2 Quarry tiles	4
3 Description	3		
4 Shapes and sizes	3		
5 Requirements	6		
6 Marking and designation	7		
7 Ordering	7		

National foreword

This Section of this British Standard has been prepared under the direction of the Clay Products Standards Committee and is the English language version of EN 186-2 'Ceramic tiles. Extruded ceramic tiles with a water absorption of $3\% < E \leq 6\%$ (Group IIa) Part-2' published by the European Committee for Standardization (CEN).

EN 186-2 was produced as a result of international discussion in which the UK took an active part.

This Section covers requirements only for certain specific products within the stated water absorption range (see clause 1). For all other tiles in this range see Part 3 : Section 3.1.

Attention is drawn to the use in this standard of the comma as a decimal marker. This is to accord with European practice, but it should be noted that it is current practice in British Standards to use a full point on the baseline as a decimal marker.

Additional information. When marking or specifying a product (see 6.1 and 6.2) the manufacturer may mark or specify by reference to either the European Standard or the British Standard.

Compliance with a British Standard does not of itself confer immunity from legal obligations.

* Untitled in the text of EN 186-2.