

Locking devices for ball and socket couplings of string insulator units — Dimensions and tests

The European Standard EN 60372:2004 has the status of a British Standard

ICS 17.220.99; 29.035.99

National foreword

This British Standard is the official English language version of EN 60372:2004. It is identical with IEC 60372:1984, including amendment 1:1991 and amendment 2:2003. It supersedes BS 3288-4:1989 which will be withdrawn on 2007-06-01.

The UK participation in its preparation was entrusted by Technical Committee PEL/36, Insulators for power systems, to Subcommittee PEL/36/2, Line insulators, which has the responsibility to:

- aid enquirers to understand the text;
- present to the responsible international/European committee any enquiries on the interpretation, or proposals for change, and keep the UK interests informed;
- monitor related international and European developments and promulgate them in the UK.

A list of organizations represented on this subcommittee can be obtained on request to its secretary.

Cross-references

The British Standards which implement international or European publications referred to in this document may be found in the *BSI Catalogue* under the section entitled “International Standards Correspondence Index”, or by using the “Search” facility of the *BSI Electronic Catalogue* or of British Standards Online.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

Compliance with a British Standard does not of itself confer immunity from legal obligations.

Summary of pages

This document comprises a front cover, an inside front cover, the EN title page, pages 2 to 17 and a back cover.

The BSI copyright notice displayed in this document indicates when the document was last issued.

Amendments issued since publication

Amd. No.	Date	Comments

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 5 August 2004

© BSI 5 August 2004

ISBN 0 580 44169 5