



INTERNATIONAL STANDARD ISO 16322-2:2005
TECHNICAL CORRIGENDUM 1

Published 2007-10-15

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION

Textiles — Determination of spirality after laundering —
Part 2:
Woven and knitted fabrics

TECHNICAL CORRIGENDUM 1

Textiles — Détermination du vrillage après lavage —

Partie 2: Étoffes tissées ou tricotées

RECTIFICATIF TECHNIQUE 1

Technical Corrigendum 1 to ISO 16322-2:2005 was prepared by Technical Committee ISO/TC 38, *Textiles*, SC 2, *Cleansing, finishing and water resistance tests*.

Page 2, 5.7

Replace 5.7 with the following:

5.7 Marking template, of dimensions (380 × 380) mm, (680 × 380) mm or (580 × 510) mm.

Page 3, 7.3.1

At the end of the second paragraph, add “[see Figure 6 a)]” so that the sentence reads:

Place a 580 mm × 510 mm template on the fabric with the long direction parallel to the selvage [see Figure 6 a)].

Page 3, 7.3.2

After the second sentence of second paragraph, add “[see Figure 6 b)]” so that the sentence reads:

Turn seams to the inside, forming an open-ended bag or pillowcase-type specimen to simulate a garment panel [see Figure 6 b)].

Replace the third paragraph with the following:

Fold and stitch the unsewn edge of the specimen to make a 12 mm hemmed edge [see Figure 6 c)].

At the end of the fourth paragraph, add “[see Figure 6 c)]” so that the sentence reads:

Measure and record distances along the seam lines, AB and CD, of each specimen [see Figure 6 c)].

Page 4, 9.2.1.2

In the first sentence of the first paragraph, change “(see Figure 1)” to “(see Figure 3)”.

Replace the second and third paragraphs by the following:

Place the horizontal leg of a right-angle device along line AD so that the second leg is perpendicular downward from point B. Mark point A'. Move the right-angle device horizontally along line AD and mark point D' downward from point C (see Figure 3).