



INTERNATIONAL STANDARD ISO 286-2:2010
TECHNICAL CORRIGENDUM 1

Published 2013-08-01

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION

**Geometrical product specifications (GPS) — ISO code system
for tolerances on linear sizes —**

**Part 2:
Tables of standard tolerance classes and limit deviations for
holes and shafts**

TECHNICAL CORRIGENDUM 1









*Spécification géométrique des produits (GPS) — Système de codification ISO pour les tolérances sur les
tailles linéaires —*

Partie 2: Tableaux des classes de tolérance normalisées et des écarts limites des alésages et des arbres

RECTIFICATIF TECHNIQUE 1

Technical Corrigendum 1 to ISO 286-2:2010 was prepared by Technical Committee ISO/TC 213, *Dimensional
and geometrical product specifications and verifications*.

Replace Figure 1 by the following:

Limit deviation							
A to G	H	JS	J	K	M	N	P to ZC
 $ES = EI + IT$ $EI > 0$ (see Table 2)	 $ES = 0 + IT$ $EI = 0$	 $ES = +IT/2$ $EI = -IT/2$	 $ES > 0$ (see Table 2)	 $ES < 0$ (see Table 2 and 3)	 ES (see Table 2 and 3) $EI = ES - IT$	 $ES < 0$ (see Table 3)	 $ES < 0$ (see Table 3)
NOTE 1 IT, see Table 1. NOTE 2 The represented tolerance intervals correspond approximately to a nominal size range of above 10 mm up to and including 18 mm.							

Key

- 1 K1 to K3, and also K4 to K8, for nominal size ≤ 3 mm
- 2 K4 to K8, for sizes for which $3 \text{ mm} < \text{nominal size} \leq 500 \text{ mm}$
- 3 K9 to K18, and also K4 to K8 for nominal size $> 500 \text{ mm}$
- 4 M1 to M6
- 5 M9 to M18, and also M7 to M8 for nominal size $> 500 \text{ mm}$
- 6 N1 to N8 and also N9 to N18 for sizes for which $1 \text{ mm} < \text{nominal size} \leq 3 \text{ mm}$, as well as nominal size $> 500 \text{ mm}$
- 7 N9 to N18 for sizes for which $3 \text{ mm} < \text{nominal size} \leq 500 \text{ mm}$