
**Bonded abrasive products —
Dimensions —**

Part 4:

Grinding wheels for surface grinding/peripheral grinding

Produits abrasifs agglomérés — Dimensions —

Partie 4: Meules pour rectification plane/meulage tangentiel



Contents	Page
1 Scope	1
2 Normative references	2
3 Dimensions.....	3
3.1 Type 1: Straight grinding wheel	3
3.2 Type 5: Wheel recessed on one side	4
3.3 Type 7: Wheel recessed on both sides.....	6
3.4 Type 20: Wheel relieved on one side	8
3.5 Type 21: Wheel relieved on both sides.....	8
3.6 Type 22: Wheel relieved on one side and recessed on the other side	9
3.7 Type 23: Wheel relieved and recessed on one side	9
3.8 Type 24: Wheel relieved and recessed on one side and recessed on the other side.....	10
3.9 Type 25: Wheel relieved and recessed on one side and relieved on the other side	11
3.10 Type 26: Wheel relieved and recessed on both sides.....	12
3.11 Type 38: Hubbed wheel.....	13
3.12 Type 39: Double hubbed wheel	13
4 Designation	15
5 Specifications.....	15
5.1 Tolerances	15
5.2 Balancing.....	15
5.3 Marking	15
Bibliography	16

© ISO 1999

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization
Case postale 56 • CH-1211 Genève 20 • Switzerland
Internet iso@iso.ch

Printed in Switzerland