
**Information technology — Data interchange
on 120 mm optical disk cartridges using
phase change PD format — Capacity:
650 Mbytes per cartridge**

*Technologies de l'information — Échange de données sur cartouches de
disque optique de 120 mm de diamètre utilisant un format PD de
changement de phase — Capacité: 650 Mbytes par cartouche*

Contents

Section 1 - General	1
1 Scope	1
2 Conformance	1
2.1 Optical disk cartridge	1
2.2 Generating system	1
2.3 Receiving system	1
2.4 Compatibility statement	1
3 Normative reference	1
4 Definitions	2
4.1 addressable track	2
4.2 band	2
4.3 case	2
4.4 Channel bit	2
4.5 Clamping Zone	2
4.6 control track	2
4.7 Cyclic Redundancy Check (CRC)	2
4.8 defect management	2
4.9 disk reference plane	2
4.10 embossed mark	2
4.11 entrance surface	2
4.12 Error Correction Code (ECC)	2
4.13 field	2
4.14 format	2
4.15 interleaving	2
4.16 land and groove	2
4.17 mark	2
4.18 one-beam overwrite	2
4.19 optical disk	2
4.20 optical disk cartridge (ODC)	2
4.21 phase change (PC)	2
4.22 physical track	2
4.23 pitch	2
4.24 polarization	2
4.25 read power	3
4.26 recording layer	3
4.27 Reed-Solomon code	3
4.28 rewritable disk	3
4.29 sector	3

© ISO/IEC 1997

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

ISO/IEC Copyright Office • Case Postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland