

ISO/IEC 24739-1
(First edition – 2009)

Information technology – AT attachment with packet interface-7 –
Part 1: Register delivered command set, logical register set (ATA/ATAPI-7 V1)

C O R R I G E N D U M 1

5.15.1 Signature for devices not implementing the PACKET command feature set

Delete, in the existing table "PACKET command feature set", the last entry:

Device	00h
--------	-----

5.15.2 Signature for devices implementing the PACKET command feature set

Delete, in the existing table "PACKET command feature set", the last entry:

Device	000x0000b where x equals 0 except when responding to a DEVICE RESET, IDENTIFY DEVICE, or READ SECTOR(S) command. For a DEVICE RESET, IDENTIFY DEVICE, or READ SECTOR(S) command the value of x is not changed from that existing when the command is written to the Command register.
--------	---

5.15.3 Reserved signatures for Serial ATA working groups

Replace the second sentence of the first paragraph as follows:

The use of these signatures is not defined by this standard.

6.10.4.8.6 Word 7: Command/features set supported

Replace the existing fifth paragraph of this subclause by the following:

Word 7 bit 4 is cleared to zero to disable support for the Power-up in Standby feature set and has the effect of clearing bits (6:5) to zero in word 83 and word 86 of the IDENTIFY DEVICE or IDENTIFY PACKET DEVICE response. If Power-up in Standby has been enabled by a jumper, these bits shall not be cleared.

6.18.9 Word 0: General configuration

Replace, in the existing fifth paragraph, the term "IDENTIFY DEVICE" by "IDENTIFY PACKET DEVICE".