

INTERNATIONAL STANDARD

ISO/IEC 9314-5

First edition
1995-02-01

Information technology — Fibre Distributed Data Interface (FDDI) — Part 5: Hybrid Ring Control (HRC)

*Technologies de l'information — Interface de données distribuées sur
fibre (FDDI) —*

Partie 5: Commande hybride par anneau (HRC)



Reference number
ISO/IEC 9314-5:1995(E)

Contents

Foreword	iv
1 Scope	1
2 Normative references	1
3 Definitions	2
4 Conventions and abbreviations	6
4.1 Conventions	6
4.2 Abbreviations	7
5 General description	8
5.1 Traffic types	9
5.2 Transmission facilities	9
5.3 Bandwidth management	11
5.4 Station structure	12
6 HRC services	16
6.1 PHY to H-MUX services	17
6.2 H-MUX to MAC services	18
6.3 H-MUX to P-MAC services	19
6.4 H-MUX to I-MAC services	21
6.5 H-MUX to SMT services	24
6.6 I-MAC to CS-MUX services	30
6.7 I-MAC to SMT services	32
7 Facilities	34
7.1 H-MUX symbol set	34
7.2 Cycle	34
7.3 HRC protocol parameters	38
7.4 Variables	39
7.5 Timers	42
7.6 Counters	43
7.7 Signals	43
7.8 Functions	44
8 Operation	44
8.1 Ring operation overview	44
8.2 Error recovery	50
8.3 Structure	53
8.4 Cycle acquisition	57
8.5 Cycle generation process	67
8.6 Cycle exchange process	84

© ISO/IEC 1995

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization

Case postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland